



<b>TEST REPORT</b> <b>IEC 62471</b> <b>Photobiological safety of lamps and lamp systems</b>	
Report Reference No. .... :	GZES120800762131
Date of issue ..... :	2012-08-22
Total number of pages ..... :	17
<b>CB Testing Laboratory</b> ..... :	SGS-CSTC Standards Technical Services Co., Ltd. - E&E Lab Guangzhou
Address ..... :	198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, 510663 Guangdong, China
<b>Applicant's name</b> ..... :	Guangzhou Hongli Opto-Electronic Co., Ltd.
Address ..... :	Airport High-Tech Industrial Zone, Jingu South Road(Intersection of Xianke 1 <sup>st</sup> Rd), Huadong Town, Huadu District, Guangzhou, China
<b>Test specification:</b>	
Standard ..... :	IEC 62471: 2006 (First Edition)
Test procedure..... :	Test report
Non-standard test method..... :	N/A
<b>Test Report Form No.</b> ..... :	IEC62471A
TRF Originator ..... :	VDE Testing and Certification Institute
Master TRF ..... :	Dated 2009-05
<b>Copyright © 2009 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.	
<b>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</b>	
<b>Test item description</b> ..... :	SMD LED
Trade Mark..... :	--
Manufacturer..... :	Same as applicant
Model/Type reference ..... :	HL-A-5630D34W-S1-HR1
Ratings..... :	3,0-3,8 Vd.c., 150 mA

Testing procedure and testing location:	
<input checked="" type="checkbox"/> <b>Testing Laboratory:</b>	Refer to page 1.
Testing location/ address.....:	Refer to page 1.
<input type="checkbox"/> <b>Associated CB Laboratory:</b>	
Testing location/ address.....:	
Tested by (name + signature) .....	Tim Ding 
Approved by (+ signature) .....	Ivory Lu 
<input type="checkbox"/> Testing procedure: TMP	
Tested by (name + signature) .....	
Approved by (+ signature) .....	
Testing location/ address.....:	
<input type="checkbox"/> Testing procedure: WMT	
Tested by (name + signature) .....	
Witnessed by (+ signature).....	
Approved by (+ signature).....	
Testing location/ address.....:	
<input type="checkbox"/> Testing procedure: SMT	
Tested by (name + signature) .....	
Approved by (+ signature).....	
Supervised by (+ signature).....	
Testing location/ address.....:	
<input type="checkbox"/> Testing procedure: RMT	
Tested by (name + signature) .....	
Approved by (+ signature).....	
Supervised by (+ signature).....	
Testing location/ address.....:	



**Summary of testing:**

Due to the physical properties of the Lamp, this product does not contain any radiation above 800nm. Therefore the measured spectral range has been limited from 200nm up to and including 800nm.

The tests were conducted under 150 mA.

**Tests performed (name of test and test clause):**

4.3.1 Actinic UV hazard exposure limit for the skin and eye

4.3.2 Near-UV hazard exposure limit for eye

4.3.3 Retinal blue light hazard exposure limit

4.3.5 Retinal thermal hazard exposure limit

**Testing location:**

Refer to page 1.

**Summary of compliance with National Differences:**

--

**Copy of marking plate:**

--

<b>Test item particulars</b> .....	
Tested lamp .....	<input checked="" type="checkbox"/> continuous wave lamps <input type="checkbox"/> pulsed lamps
Tested lamp system .....	
Lamp classification group .....	<input checked="" type="checkbox"/> exempt <input type="checkbox"/> risk 1 <input type="checkbox"/> risk 2 <input type="checkbox"/> risk 3
Lamp cap .....	--
Bulb .....	--
Rated of the lamp .....	--
Furthermore marking on the lamp.....	--
Seasoning of lamps according IEC standard .....	--
Used measurement instrument.....	Ref. to List of test equipment used
Temperature by measurement.....	25 ± 5 °C
Information for safety use.....	--
<b>Possible test case verdicts:</b>	
– test case does not apply to the test object ..... : N/A	
– test object does meet the requirement..... : P (Pass)	
– test object does not meet the requirement..... : F (Fail)	
<b>Testing:</b>	
Date of receipt of test item .....	: 2012-08-15
Date (s) of performance of tests.....	: 2012-08-15 to 2012-08-22
<b>General remarks:</b>	
<p>The test results presented in this report relate only to the object tested.  This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.  "(See Enclosure #)" refers to additional information appended to the report.  "(See appended table)" refers to a table appended to the report.  Throughout this report a comma (point) is used as the decimal separator.  List of test equipment must be kept on file and available for review.</p> <p>When determining for test conclusion, measurement uncertainty of tests has been considered.</p> <p>This document is issued by the company under its General Conditions of Service accessible at <a href="http://www.sgs.com/terms_and_conditions.htm">http://www.sgs.com/terms_and_conditions.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.</p> <p>Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.</p> <p>Unless otherwise stated: (a) the results shown in this document refer only to the sample(s) tested and (b) such sample(s) are retained for 12 months. This document cannot be reproduced except in full, without prior approval of the company.</p>	

**General product information:**

The product can emit cool white light when powered.

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict
<b>4</b>	<b>EXPOSURE LIMITS</b>		--
4.1	General		P
	The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure		P
	Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4 \text{ cd}\cdot\text{m}^{-2}$	see clause 4.3	P
4.3	Hazard exposure limits		P
4.3.1	Actinic UV hazard exposure limit for the skin and eye		P
	The exposure limit for effective radiant exposure is $30 \text{ J}\cdot\text{m}^{-2}$ within any 8-hour period		P
	To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broad-band source, the effective integrated spectral irradiance, $E_s$ , of the light source shall not exceed the levels defined by:		P
	$E_s \cdot t = \sum_{200}^{400} \sum_t E_\lambda(\lambda, t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 30 \quad \text{J}\cdot\text{m}^{-2}$		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by:		P
	$t_{\max} = \frac{30}{E_s} \quad \text{s}$		P
4.3.2	Near-UV hazard exposure limit for eye		P
	For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed $10000 \text{ J}\cdot\text{m}^{-2}$ for exposure times less than 1000 s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, $E_{UVA}$ , shall not exceed $10 \text{ W}\cdot\text{m}^{-2}$ .		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by:		P
	$t_{\max} = \frac{10\,000}{E_{UVA}}$		P
4.3.3	Retinal blue light hazard exposure limit		P
	To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(\lambda)$ , i.e., the blue-light weighted radiance, $L_B$ , shall not exceed $0.000 \text{ W}\cdot\text{m}^{-2}\cdot\text{s}$ . For $0.71997 \leq \lambda \leq 0.72 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.405 \leq \lambda \leq 0.41 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.41 \leq \lambda \leq 0.42 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.42 \leq \lambda \leq 0.43 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.43 \leq \lambda \leq 0.44 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.44 \leq \lambda \leq 0.45 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.45 \leq \lambda \leq 0.46 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.46 \leq \lambda \leq 0.47 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.47 \leq \lambda \leq 0.48 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.48 \leq \lambda \leq 0.49 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.49 \leq \lambda \leq 0.50 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.50 \leq \lambda \leq 0.51 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.51 \leq \lambda \leq 0.52 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.52 \leq \lambda \leq 0.53 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.53 \leq \lambda \leq 0.54 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.54 \leq \lambda \leq 0.55 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.55 \leq \lambda \leq 0.56 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.56 \leq \lambda \leq 0.57 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.57 \leq \lambda \leq 0.58 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.58 \leq \lambda \leq 0.59 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.59 \leq \lambda \leq 0.60 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.60 \leq \lambda \leq 0.61 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.61 \leq \lambda \leq 0.62 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.62 \leq \lambda \leq 0.63 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.63 \leq \lambda \leq 0.64 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.64 \leq \lambda \leq 0.65 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.65 \leq \lambda \leq 0.66 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.66 \leq \lambda \leq 0.67 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.67 \leq \lambda \leq 0.68 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.68 \leq \lambda \leq 0.69 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.69 \leq \lambda \leq 0.70 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.70 \leq \lambda \leq 0.71 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.71 \leq \lambda \leq 0.72 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.72 \leq \lambda \leq 0.73 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.73 \leq \lambda \leq 0.74 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.74 \leq \lambda \leq 0.75 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.75 \leq \lambda \leq 0.76 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.76 \leq \lambda \leq 0.77 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.77 \leq \lambda \leq 0.78 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.78 \leq \lambda \leq 0.79 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.79 \leq \lambda \leq 0.80 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.80 \leq \lambda \leq 0.81 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.81 \leq \lambda \leq 0.82 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.82 \leq \lambda \leq 0.83 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.83 \leq \lambda \leq 0.84 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.84 \leq \lambda \leq 0.85 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.85 \leq \lambda \leq 0.86 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.86 \leq \lambda \leq 0.87 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.87 \leq \lambda \leq 0.88 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.88 \leq \lambda \leq 0.89 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.89 \leq \lambda \leq 0.90 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.90 \leq \lambda \leq 0.91 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.91 \leq \lambda \leq 0.92 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.92 \leq \lambda \leq 0.93 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.93 \leq \lambda \leq 0.94 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.94 \leq \lambda \leq 0.95 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.95 \leq \lambda \leq 0.96 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.96 \leq \lambda \leq 0.97 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.97 \leq \lambda \leq 0.98 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.98 \leq \lambda \leq 0.99 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $0.99 \leq \lambda \leq 1.00 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $\lambda < 0.405 \mu\text{m}$ , $B(\lambda) = 0.000$ . For $\lambda > 1.00 \mu\text{m}$ , $B(\lambda) = 0.000$ .		P

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict
	$L_B \cdot t = \sum_{300}^{700} \sum E_{\lambda}(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 10^6 \quad \text{J} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	for $t \leq 10^4 \text{ s}$ $t_{\max} = \frac{10^6}{L_B}$	P
	$L_B = \sum_{300}^{700} E_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 10^2 \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	for $t > 10^4 \text{ s}$	N/A
4.3.4	Retinal blue light hazard exposure limit - small source		N/A
	Thus the spectral irradiance at the eye $E_{\lambda}$ , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by:	see table 4.2	N/A
	$E_B \cdot t = \sum_{300}^{700} \sum E_{\lambda}(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \quad \text{J} \cdot \text{m}^{-2}$	for $t \leq 100 \text{ s}$	N/A
	$E_R = \sum_{300}^{700} E_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 1 \quad \text{W} \cdot \text{m}^{-2}$	for $t > 100 \text{ s}$	N/A
4.3.5	Retinal thermal hazard exposure limit		P
	To protect against retinal thermal injury, the integrated spectral radiance of the light source, $L_{\lambda}$ , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by:		P
	$L_{IR} = \sum_{780}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6000}{\alpha} \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	( $10 \mu\text{s} \leq t \leq 10 \text{ s}$ )	P
4.3.6	Retinal thermal hazard exposure limit – weak visual stimulus		N/A
	For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, $L_{IR}$ , as viewed by the eye for exposure times greater than 10 s shall be limited to:		N/A
	$L_{IR} = \sum_{780}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6000}{\alpha} \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	$t > 10 \text{ s}$	N/A
4.3.7	Infrared radiation hazard exposure limits for the eye		N/A
	The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, $E_{IR}$ , over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed:		N/A
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 18000 \cdot t^{-0,75} \quad \text{W} \cdot \text{m}^{-2}$	$t \leq 1000 \text{ s}$	N/A
	For times greater than 1000 s the limit becomes:		N/A

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 100 \quad \text{W} \cdot \text{m}^{-2}$	$t > 1000 \text{ s}$	N/A
4.3.8	Thermal hazard exposure limit for the skin		N/A
	Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to:		N/A
	$E_{H \cdot t} = \sum_{380}^{3000} \sum_t E_{\lambda}(\lambda, t) \cdot \Delta t \cdot \Delta\lambda \leq 20\,000 \cdot t^{0,25} \quad \text{J} \cdot \text{m}^{-2}$		N/A
<b>5</b>	<b>MEASUREMENT OF LAMPS AND LAMP SYSTEMS</b>		--
5.1	Measurement conditions		P
	Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification.		P
5.1.1	Lamp ageing (seasoning)		N/A
	Seasoning of lamps shall be done as stated in the appropriate IEC lamp standard.		N/A
5.1.2	Test environment		P
	For specific test conditions, see the appropriate IEC lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations.		P
5.1.3	Extraneous radiation		P
	Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results.		P
5.1.4	Lamp operation		P
	Operation of the test lamp shall be provided in accordance with:		P
	– the appropriate IEC lamp standard, or		N/A
	– the manufacturer's recommendation		P
5.1.5	Lamp system operation		P
	The power source for operation of the test lamp shall be provided in accordance with:		P
	– the appropriate IEC standard, or		N/A
	– the manufacturer's recommendation		P
5.2	Measurement procedure		P
5.2.1	Irradiance measurements		P
	Minimum aperture diameter 7mm.		P



<b>IEC 62471</b>			
Clause	Requirement + Test	Result – Remark	Verdict
	Maximum aperture diameter 50 mm.		P
	The measurement shall be made in that position of the beam giving the maximum reading.		P
	The measurement instrument is adequate calibrated.		P
5.2.2	Radiance measurements		P
5.2.2.1	Standard method		N/A
	The measurements made with an optical system.		N/A
	The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument.		N/A
5.2.2.2	Alternative method		P
	Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements.		P
5.2.3	Measurement of source size		P
	The determination of $\theta$ , the angle subtended by a source, requires the determination of the 50% emission points of the source.		P
5.2.4	Pulse width measurement for pulsed sources		N/A
	The determination of $t_p$ , the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value.		N/A
5.3	Analysis methods		P
5.3.1	Weighting curve interpolations		P
	To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired.	see table 4.1	P
5.3.2	Calculations		P
	The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy.		P
5.3.3	Measurement uncertainty		P
	The quality of all measurement results must be quantified by an analysis of the uncertainty.	see Annex C in the norm	P
<b>6</b>	<b>LAMP CLASSIFICATION</b>		--

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict
	For the purposes of this standard it was decided that the values shall be reported as follows:	see table 6.1	P
	– for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm		N/A
	– for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm	r = 200 mm	P
6.1	Continuous wave lamps		P
6.1.1	Except Group		P
	In the exempt group are lamps, which do not pose any photobiological hazard. The requirement is met by any lamp that does not pose:		P
	– an actinic ultraviolet hazard ( $E_S$ ) within 8-hours exposure (30000 s), nor		P
	– a near-UV hazard ( $E_{UVA}$ ) within 1000 s, (about 16 min), nor		P
	– a retinal blue-light hazard ( $L_B$ ) within 10000 s (about 2,8 h), nor		P
	– a retinal thermal hazard ( $L_R$ ) within 10 s, nor		P
	– an infrared radiation hazard for the eye ( $E_{IR}$ ) within 1000 s		N/A
6.1.2	Risk Group 1 (Low-Risk)		N/A
	In this group are lamps, which exceeds the limits for the except group but that does not pose:		N/A
	– an actinic ultraviolet hazard ( $E_S$ ) within 10000 s, nor		N/A
	– a near ultraviolet hazard ( $E_{UVA}$ ) within 300 s, nor		N/A
	– a retinal blue-light hazard ( $L_B$ ) within 100 s, nor		N/A
	– a retinal thermal hazard ( $L_R$ ) within 10 s, nor		N/A
	– an infrared radiation hazard for the eye ( $E_{IR}$ ) within 100 s		N/A
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 100 s are in Risk Group 1.		N/A
6.1.3	Risk Group 2 (Moderate-Risk)		N/A
	This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose:		N/A
	– an actinic ultraviolet hazard ( $E_S$ ) within 1000 s exposure, nor		N/A

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict
	– a near ultraviolet hazard ( $E_{UVA}$ ) within 100 s, nor		N/A
	– a retinal blue-light hazard ( $L_B$ ) within 0,25 s (aversion response), nor		N/A
	– a retinal thermal hazard ( $L_R$ ) within 0,25 s (aversion response), nor		N/A
	– an infrared radiation hazard for the eye ( $E_{IR}$ ) within 10 s		N/A
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 10 s are in Risk Group 2.		N/A
6.1.4	Risk Group 3 (High-Risk)		N/A
	Lamps which exceed the limits for Risk Group 2 are in Group 3.		N/A
6.2	Pulsed lamps		N/A
	Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25 s.		N/A
	A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer.		N/A
	The risk group determination of the lamp being tested shall be made as follows:		N/A
	– a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk)		N/A
	– for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group		N/A
	– for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission		N/A

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict

Table 4.1	Spectral weighting function for assessing ultraviolet hazards for skin and eye			P
Wavelength <sup>1</sup> $\lambda$ , nm	UV hazard function $S_{uv}(\lambda)$	Wavelength $\lambda$ , nm	UV hazard function $S_{uv}(\lambda)$	
200	0,030	313*	0,006	
205	0,051	315	0,003	
210	0,075	316	0,0024	
215	0,095	317	0,0020	
220	0,120	318	0,0016	
225	0,150	319	0,0012	
230	0,190	320	0,0010	
235	0,240	322	0,00067	
240	0,300	323	0,00054	
245	0,360	325	0,00050	
250	0,430	328	0,00044	
254*	0,500	330	0,00041	
255	0,520	333*	0,00037	
260	0,650	335	0,00034	
265	0,810	340	0,00028	
270	1,000	345	0,00024	
275	0,960	350	0,00020	
280*	0,880	355	0,00016	
285	0,770	360	0,00013	
290	0,640	365*	0,00011	

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict

Table 4.2	Spectral weighting functions for assessing retinal hazards from broadband optical sources	P
Wavelength nm	Blue-light hazard function B ( $\lambda$ )	Burn hazard function R ( $\lambda$ )
300	0,01	--
305	0,01	--
310	0,01	--
315	0,01	--
320	0,01	--
325	0,01	--
330	0,01	--
335	0,01	--
340	0,01	--
345	0,01	--
350	0,01	--
355	0,01	--
360	0,01	--
365	0,01	--
370	0,01	--
375	0,01	--
380	0,01	0,1
385	0,013	0,13
390	0,025	0,25
395	0,05	0,5
400	0,10	1,0
405	0,20	2,0
410	0,40	4,0
415	0,80	8,0
420	0,90	9,0
425	0,95	9,5
430	0,98	9,8
435	1,00	10,0
440	1,00	10,0
445	0,97	9,7
450	0,94	9,4
455	0,90	9,0
460	0,80	8,0
465	0,70	7,0
470	0,62	6,2
475	0,55	5,5
480	0,45	4,5
485	0,40	4,0
490	0,22	2,2
495	0,16	1,6
500-600	$10^{[(450-\lambda)/50]}$	1,0
600-700	0,001	1,0
700-1050		$10^{[(700-\lambda)/500]}$
1050-1150		0,2
1150-1200		$0,2 \cdot 10^{0,02(1150-\lambda)}$

<b>IEC 62471</b>			
Clause	Requirement + Test	Result – Remark	Verdict
<b>Table 4.2</b>	Spectral weighting functions for assessing retinal hazards from broadband optical sources		P
	1200-1400		0,02

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict

Table 5.4 Summary of the ELs for the surface of the skin or cornea (irradiance based values)					P
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Limiting aperture rad (deg)	EL in terms of constant irradiance $W \cdot m^{-2}$
Actinic UV skin & eye	$E_S = E \cdot S(\lambda) \cdot$	200 – 400	< 30000	1,4 (80)	30/t
Eye UV-A	$E_{UVA} = E \cdot$	315 – 400	1000 >1000	1,4 (80)	10000/t 10
Blue-light small source	$E_B = E \cdot B(\lambda) \cdot$	300 – 700	100 >100	< 0,011	100/t 1,0
Eye IR	$E_{IR} = E \cdot$	780 – 3000	1000 >1000	1,4 (80)	18000/t <sup>0,75</sup> 100
Skin thermal	$E_H = E \cdot$	380 – 3000	< 10	2 sr	20000/t <sup>0,75</sup>

Table 5.5 Summary of the ELs for the retina (radiance based values)					P
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Field of view radians	EL in terms of constant radiance $W \cdot m^{-2} \cdot sr^{-1}$
Blue light	$L_B = L \cdot B(\lambda) \cdot$	300 – 700	0,25 – 10	0,011 • (t/10)	10 <sup>6</sup> /t
			10-100	0,011	10 <sup>6</sup> /t
			100-10000	0,0011 • t	10 <sup>6</sup> /t
			10000	0,1	100
Retinal thermal	$L_R = L \cdot R(\lambda) \cdot$	380 – 1400	< 0,25	0,0017	50000/(t <sup>0,25</sup> )
			0,25 – 10	0,011 • (t/10)	50000/(t <sup>0,25</sup> )
Retinal thermal (weak visual stimulus)	$L_{IR} = L \cdot R(\lambda) \cdot$	780 – 1400	> 10	0,011	6000/

IEC 62471			
Clause	Requirement + Test	Result – Remark	Verdict


Table 6.1		Emission limits for risk groups of continuous wave lamps								P
Risk	Action spectrum	Symbol	Units	Emission Measurement						
				Exempt		Low risk		Mod risk		
				Limit	Result	Limit	Result	Limit	Result	
Actinic UV	$S_{UV}(\ )$	$E_s$	$W \cdot m^{-2}$	0,001	0	0,003	--	0,03	--	
Near UV		$E_{UVA}$	$W \cdot m^{-2}$	10	0	33	--	100	--	
Blue light	$B(\ )$	$L_B$	$W \cdot m^{-2} \cdot sr^{-1}$	100	58,1	10000	--	4000000	--	
Blue light, small source	$B(\ )$	$E_B$	$W \cdot m^{-2}$	1,0*	--	1,0	--	400	--	
Retinal thermal	$R(\ )$	$L_R$	$W \cdot m^{-2} \cdot sr^{-1}$	28000/	10316,9	28000/	--	71000/	--	
Retinal thermal, weak visual stimulus**	$R(\ )$	$L_{IR}$	$W \cdot m^{-2} \cdot sr^{-1}$	6000/	--	6000/	--	6000/	--	
IR radiation, eye		$E_{IR}$	$W \cdot m^{-2}$	100	--	570	--	3200	--	
* Small source defined as one with $< 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian. ** Involves evaluation of non-GLS source										



**Photo documentation**

Details of: [View for the product](#)

---

<p>View:</p> <p><input checked="" type="checkbox"/> general</p> <p><input type="checkbox"/> front</p> <p><input type="checkbox"/> rear</p> <p><input type="checkbox"/> right</p> <p><input type="checkbox"/> left</p> <p><input type="checkbox"/> top</p> <p><input type="checkbox"/> bottom</p> <p><input type="checkbox"/> Internal</p>	
---	---

--- END OF REPORT ---