

TEST REPORT IEC TR 62778 Application of IEC TR 62778 for the assessment of blue light hazard to light sources and luminaires	
Report reference No	SZ2211027-55191E-SF
Compiled by (+ signature)	Test Engineer: Zero Gao
Approved by (+ signature)	Team Leader: Harrison Huang
Date of issue	2021-11-01
Testing laboratory	Bay Area Compliance Laboratories Corp.(Dongguan)
Address	No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China
Testing location	Same as above
Applicant	Hongli Zhihui Group Co., Ltd. Guangzhou Branch
Address	Room 316, Building 2, No.1, Xianke Yi Road, Huadong Town, Huadu District, Guangzhou, China.
Standard	IEC TR 62778:2014
Test sample(s) received.....	2021-10-28
Test in period.....	2021-10-30
Procedure deviation	N.A.
Non-standard test method	N.A.
Type of test object	LED package
Trademark	N.A.
Model/type reference	HL-ES-3032S23V405-B2-S1
Manufacturer.....	Hongli Zhihui Group Co., Ltd. Guangzhou Branch Room 316, Building 2, No.1, Xianke Yi Road, Huadong Town, Huadu District, Guangzhou, China.
Rating	Input: 3Vdc, 150mA.
Copy of marking plate:	None

Test item particulars

Product evaluated	<input checked="" type="checkbox"/> LED package <input type="checkbox"/> LED module <input type="checkbox"/> Lamp <input type="checkbox"/> Luminaire
Rated voltage (V)	See rating
Rated current (mA)	See rating
Rated Luminance (Mcd/m²)	Not specified
Component report data used	<input checked="" type="checkbox"/> Not applicable <input type="checkbox"/> LED package <input type="checkbox"/> LED module <input type="checkbox"/> Lamp

Possible test case verdicts:
-test case does not apply to the test object.....: N(.A.)
-test object does meet the requirement.....: P(ass)
-test object does not meet the requirement.....: F(all)

General remarks:
The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.
"(See Enclosure #)" refers to additional information appended to the report.
"(See appended table)" refers to a table appended to the report.
Throughout this report a point is used as the decimal separator.
List of test equipment must be kept on file and available for review.

Remark:
Appendix A - EUT Photos

General product information:
"EUT" as referred in this report is a LED package. And the input rating is 3Vdc, 150mA.

IEC TR 62778			
Clause	Requirement + Test	Result - Remark	Verdict

TABLE: Spectroradiometric measurement			P
	Measurement performed on:	<input checked="" type="checkbox"/> LED package <input type="checkbox"/> LED module <input type="checkbox"/> Lamp <input type="checkbox"/> Luminaire	—
	Model number	HL-ES-3032S23V405-B2-S1	—
	Test voltage (V).....	3Vdc	—
	Test current (mA)	150mA	—
	Test frequency (Hz).....	--	—
	Ambient, t (°C).....	24.5	—
	Measurement distance	<input checked="" type="checkbox"/> 20 cm <input type="checkbox"/> ... cm	—
	Source size	<input type="checkbox"/> Non-small: mm <input checked="" type="checkbox"/> Small: 0.85 mm	—
	Field of view	<input type="checkbox"/> 100 mrad <input type="checkbox"/> 11 mrad <input checked="" type="checkbox"/> 4.2 mrad (for small sources)	—


Item	Symb ol	Units	Result	Remark
Correlated colour temperature	CCT	K	--	--
x/y colour coordinates	x/y		0.1735/0.0142	--
Blue light hazard radiance	L _B	W/(m ² •sr ¹)	9.978 x 10 ³	--
Blue light hazard irradiance	E _B	W/m ²	2.831 x 10 ⁻¹	--
Luminance	L	cd/m ²	8.006 x 10 ⁴	--
Illuminance	E	lx	2	--

Supplementary information: NA

	TABLE: Angular light distribution	

Appendix A - EUT Photos

The overall view of EUT



Directions:

- 1.The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
- 2.Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
- 3.Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
- 4.The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
- 5.This report cannot be reproduced except in full, without prior written approval of the Company.
- 6.This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****End of report*****